



## Small Series

MODEL	Length without Button (A)	Length with Button (B)	Thread (C)	Rod Dia. (D)	Button Dia. (E)	Cylinder (F)	Flat Width (G)	Flat Length (H)
KYN80 IF	1.85	2.25	3/8 - 32 UNEF	0.098	0.268	1.61	-	-
KYN100 IF	2.50	2.75	7/16 - 28 UNEF	0.118	0.340	2.00	-	-
KYN150 IF	2.50	2.85	7/16 - 28 UNEF	0.118	0.400	2.00	0.43	0.30
KYN150 IC			1/2 - 20 UNEF					
KYN250 IF	3.90	4.37	1/2 - 20 UNF	0.157	0.400	3.40	0.47	0.45
KYN250 IC			9/16 - 18 UNF					
KYN500	4.75	5.16	3/4 - 16 UNF	0.197	0.500	2.13	0.70	0.50
KYN1000 IF	5.12	5.62	1 - 12 UNF	0.252	0.620	4.00	0.90	0.50
KYN1115 IF	6.00	6.10	1 1/4 - 12 UNF	0.374	1.200	3.65	1.20	0.60
KYN1125 IF	6.00	6.10	1 3/8 - 12 UNF	0.374	1.200	3.65	1.30	0.60
KYN2115 IF	8.50	8.70	1 1/4 - 12 UNF	0.374	1.200	5.25	1.20	0.60
KYN2125 IF	8.50	8.70	1 3/8 - 12 UNF	0.374	1.200	5.25	1.30	0.60

## Large Series

KYN1525 IC	5.70	6.40	1-3/4 - 12 UN	0.512	1.732	3.60	1.60	0.80
KYN1550 IC	7.70	8.40	1-3/4 - 12 UN	0.512	1.732	4.75	1.60	0.80
KYN1575 IC	9.70	10.40	1-3/4 - 12 UN	0.512	1.732	5.70	1.60	0.80
KYN2050 IC	8.90	9.60	2-1/2 - 12 UN	0.750	2.250	5.50	2.75	1.00
KYN2100 IC	12.90	13.60	2-1/2 - 12 UN	0.750	2.250	7.50	2.75	1.00
KYN2150 IC	18.10	18.60	2-1/2 - 12 UN	0.750	2.250	9.50	2.75	1.00
KYN3050 IC	9.65	10.40	3-3/8 - 12 UN	0.866	3.000	5.50	-	-
KYN3100 IC	13.40	14.40	3-3/8 - 12 UN	0.866	3.000	8.00	-	-
KYN3150 IC	16.20	20.00	3-3/8 - 12 UN	0.866	3.000	9.00	-	-
KYN4050 IC	12.30	13.10	4 1/2 - 12 UN	1.375	3.750	8.00	-	-
KYN4100 IC	16.30	17.10	4 1/2 - 12 UN	1.375	3.750	10.00	-	-
KYN4150 IC	20.25	21.10	4 1/2 - 12 UN	1.375	3.750	12.00	-	-
KYN4200 IC	25.40	26.20	4 1/2 - 12 UN	1.375	3.750	14.00	-	-
KYN4250 IC	29.30	30.10	4 1/2 - 12 UN	1.375	3.750	16.00	-	-